

MOL Farm Protect 10W-40

multigrade diesel motor oil



MOL Farm Protect 10W-40 is a state-of-art lubricating oil consisting of synthetic and mineral base oils produced using modern oil refining processes and using a balanced additive system, that ensure high performance levels. It was developed to meet the stringent requirements of the engines in modern agricultural machines.

Application



High performance engines of tractors and self-propelled agricultural machines

Irrigation equipment, units

Hydraulic systems where application of engine oil is specified by the manufacturer

Features and benefits

Excellent wear protection

Improves engine reliability and provides protection to critical engine parts

Exceptional thermal and oxidation stability

Resists the ageing process and deposit formation, even at high operating temperatures, giving long oil lifetimes and reduced maintenance costs

Excellent shear stability

Maintains its favourable properties for a long period even under heavy loads and shear stresses

High-level reserve of alkalinity

Persistent acid neutralization, giving a long oil drain interval

Low volatility

Lowers engine oil consumption and reduces the emission of harmful substances

Excellent soot handling

Protection against soot deposits and bore polishing

Excellent cold flow properties

Reliable start-up, even in extreme cold conditions

Specifications and approvals

Viscosity grade: SAE 10W-40

ACEA E7

API CI-4

API SL

Global DHD-1

MAN M 3275-1

Volvo VDS-3

Tatra TDS 30/12

Renault RLD-2

MTU Type 2

Cummins CES 20078

Cummins CES 20077

MACK EO-M Plus

DDC 93K215

Deutz DQC III-10

Mack EO-N

MOL Farm Protect 10W-40

multigrade diesel motor oil



Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,872
Kinematic viscosity at 40°C [mm ² /s]	96,9
Kinematic viscosity at 100 °C [mm ² /s]	14,4
Viscosity index	153
Pour point [°C]	-39
Flash point (Cleveland) [°C]	220
Base number (BN) [mg KOH/g]	10,4

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13100022	MOL Farm Protect 10W-40 10LA	10 l plastic can
13100021	MOL Farm Protect 10W-40 50KG	60 l steel drum
13100023	MOL Farm Protect 10W-40 180KG	216.5 l steel drum

Order booking:

Please contact your local distributor or sales partner for ordering details.